



**PUYANG UNITED CHEMICAL CO., LTD.**

RM.1008 CYBER BUSINESS BUILDING,  
ZHENXING ROAD, PUYANG, HENAN, CHINA.

TEL: 0086-393-4662488

[www.united-chem.cn](http://www.united-chem.cn)

## TECHNICAL DATA SHEET

### SIS-1520

**SIS-1520** is a clear, linear triblock copolymer based on styrene and isoprene, with a polystyrene content of 15% and a Di-block content of 20%.

**SIS-1520** is used as an ingredient in formulating adhesives, sealants and coatings. It may also find use as a modifier of bitumen and polymers.

Product Specifications			
Test Items	Unit	Test Method	Sales Specification Range
Polystyrene Content	Wt%	GB/T 13646-2013	15.0 ± 2.0
Di-block Content	Wt%	SH/T 1812-2017 Appendix A	20 ± 2.0
Yellow Index		HG/T 3862-2006	≤ 6.0
Solution Viscosity (25°C, 25% Toluene)	mPa · s	SH/T 1610-2011 Appendix B	800 ~ 1600
Melt Flow Rate (200°C, 5kg)	g/10min	GB/T 3682.1-2018 Method A	13.0 ~ 17.0
Tensile Strength	MPa	SH/T 1610-2011 Appendix A	≥ 7.0
Elongation at Break	%	SH/T 1610-2011 Appendix A	≥ 1000
Hardness	Shore A	GB/T 531.1-2008	30 ± 5
Volatile Matter	Wt%	GB/T 24131-2009	≤ 0.70
Ash	Wt%	GB/T 4498.1-2013	≤ 0.20

### **PACKING**

**SIS-1520** is available in 20Kg bags.

The information in this bulletin is believed to be accurate, but all recommendations are made without warranty since the conditions of use are beyond Puyang United Chemical's control. The listed -properties are illustrative only, and not product specifications. Puyang United Chemical disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of its products in combination with other material or in any process.