



Technical Data Sheet: UCA100L

PRODUCT DESCRIPTION UCA100L is m-pentadiene based C5 Aliphatic hydrocarbon resin. It's general type C5 resin with narrow molecular weight distribution designed for hot melt adhesive(HMA) and hot melt pressure sensitive adhesive (HMPSA).

The major usages of UCA100L are tackify a variety of adhesive polymers including SIS block copolymers, EVA, natural rubber, synthetic polyisoprene, polyisobutylene, and Butyl rubber.

MAIN APPLICATION Hot Melt Adhesives Pressure Sensitive Adhesive
Solvent Based Adhesive Mouse Glue

TYPICAL PROPERTIES		
Appearance		Yellowish Granule
Color	Gardner in 50% toluene	4.0 max
Softening Point	°C	97-104
Ash Content	(wt.%)	0.05 max
Acid Value	(KOH mg/g)	0.30 max
Melt Viscosity	CPS(200 °C)	180±20
Molecular Weight	(G.P.C, Mn)	1,400
	(G.P.C, Mw)	2,600
	(G.P.C, Mz)	6,000
Heat Resistance	(180°C 3 h) Gardner	6.0 max

HS CODE: 39111000.00

CAS NO.: 64742-16-1

PACKAGING Packed in craft paper bags laminated with PE bags, 25kgs net weight and we also supply the packing according client request.

The information in this bulletin is believed to be accurate, but all recommendations are made without warranty since the conditions of use are beyond United Chemical Company's control. The listed properties are illustrative only, and not product specifications. United Chemical Company disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of its products in combination with other material or in any process.