



**PUYANG UNITED CHEMICAL CO., LTD.**

RM.1008 CYBER BUSINESS BUILDING,  
ZHENXING ROAD, PUYANG, HENAN, CHINA.

TEL: 0086-393-4662488

[www.united-chem.cn](http://www.united-chem.cn)

**TECHNICAL DATA SHEET**

Rev.2202

**OA-200**

**OA-200** is heavy acid modified C5/C9 hydrocarbon resin designed for PVC tapes. It is also widely used in paper sizing agent due to its easy emulsifying in water. It can also be used as a tackifier for road marking.

**SPECIFICATIONS**

Softening Point (Ring & Ball, °C)	97-103	ASTM E28
Initial Color(Ga)	11 Max	ASTM D 6166

**TYPICAL PROPERTIES**

Softening Point (Ring & Ball, °C)	101	ASTM E28
Initial Color(Ga)	8	ASTM D 6166
Acid Value (mgKOH/g)	17	ASTM D 974
Molecular Weight (G.P.C, Mw)	2,500	

**PACKING**

**OA-200** is available both in 25Kg multi-ply paper bags and 500kg bags.

**STORAGE**

**OA-200** should be stored in a cool, ventilated, dry place. Recommended temperature not exceeding 40°C.

The information in this bulletin is believed to be accurate, but all recommendations are made without warranty since the conditions of use are beyond Puyang United Chemical's control. The listed properties are illustrative only, and not product specifications. Puyang United Chemical disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of its products in combination with other material or in any process.