



HENAN UNITED CHEMICAL CO., LTD.

RM.1008 CYBER BUSINESS BUILDING,
ZHENXING ROAD, PUYANG, HENAN, CHINA.

TEL: 0086-393-4662488

www.united-chem.cn

TECHNICAL DATA SHEET

OA-200

OA-200 is heavy acid modified C5/C9 hydrocarbon resin designed for PVC tapes. It is also widely used in paper sizing agent due to its easy emulsifying in water. It can also be used as a tackifier for road marking.

SPECIFICATIONS

Softening Point (Ring & Ball, °C)	97-103	ASTM E28
Initial Color(Ga)	11 Max	ASTM D 6166

TYPICAL PROPERTIES

Softening Point (Ring & Ball, °C)	101	ASTM E28
Initial Color(Ga)	8	ASTM D 6166
Acid Value (mgKOH/g)	17	ASTM D 974
Molecular Weight (G.P.C, Mw)	2,500	

PACKING

OA-200 is available both in 25Kg multi-ply paper bags and 500kg bags.

STORAGE

OA-200 should be stored in a cool, ventilated, dry place. Recommended temperature not exceeding 40°C.

The information in this bulletin is believed to be accurate, but all recommendations are made without warranty since the conditions of use are beyond Henan United Chemical's control. The listed properties are illustrative only, and not product specifications. Henan United Chemical disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of its products in combination with other material or in any process.